

## Declaration of Performance

Nr. D300-02

1. **Product-type identification:** Dry-Pressed Ceramic Tiles, with water absorption  $0,5\% < E_b \leq 3\%$
2. **Intended use:** For internal and external walls and flooring
3. **Manufacturer:** Vitra Karo Sanayi ve Ticaret A.Ş.  
Şifa Mah. Hükümet Caddesi No: 5  
34941 Tuzla/İstanbul - TÜRKİYE
4. **Authorised representative:** Vitra UK Limited  
Park 34, Collett, Didcot OX11 7WB, United Kingdom
5. **System of assessment** and verification of constancy performance: System 4
6. **Declared performance:**

| Essential characteristics                        | Performance                                                                                                    | UK Designated technical specification |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------|
| Reaction to fire                                 | A1 / A1 <sub>FL</sub>                                                                                          | BS EN 14411: 2012                     |
| Release of dangerous substance, for:             |                                                                                                                |                                       |
| - Cadmium                                        | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| - Lead                                           | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| - Other                                          | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| Breaking strength                                | $\geq 1100 \text{ N}$ for thickness $\geq 7,5\text{mm}$<br>$\geq 700 \text{ N}$ for thickness $< 7,5\text{mm}$ | BS EN 14411: 2012                     |
| Slipperiness<br>-Tested according to BS EN 16165 | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| Tactility                                        | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| Bond strength/adhesion for:                      |                                                                                                                |                                       |
| - Cementitious adhesive, type C2                 | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| - Dispersion adhesive                            | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| - Reaction resin adhesive                        | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| - Mortar                                         | NPD / No Performance Determined                                                                                | BS EN 14411: 2012                     |
| Thermal shock resistance                         | Pass                                                                                                           | BS EN 14411: 2012                     |
| Durability For:                                  |                                                                                                                |                                       |
| -Internal Use                                    | Pass                                                                                                           | BS EN 14411: 2012                     |
| -External Use: freeze-thaw resistance            | Pass                                                                                                           | BS EN 14411: 2012                     |

7. The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Bayram Bülent Maşa – Quality Assurance Senior Manager  
Name and Function

BOZÜYÜK – 01.07.2025  
Place and date of issue

Signature